



Yamaha's popular and proven range of F175 Digital and Mechanical Control outboards now feature a newly designed look and integrated steering, taking these engines to the next level when it comes to power, reliability and control.

The Integrated Hydraulic Steering system is housed in a neat, sealed cylinder unit, which is built into the transom bracket of the engine, rather than being a third-party bolt-on component. This results in a simple and clean rigging set-up, and an uncluttered bilge and transom area, while exposing less components to the elements for improved long-term durability and reliability.

This new range of four-cylinder integrated steering models are ideal for all applications, including new boat packages, existing boat repowers and multi engine set-ups.

The modernised F175 outboards bring a new level of delight to boating.

Available in:

- F175LB- Integrated Hydraulic Steering(IHS) for Mech Helm, Power Trim, Tilt & Limiter, Transom height - Long
- F175XB- Integrated Hydraulic Steering(IHS) for Mech Helm, Power Trim, Tilt & Limiter, Transom height - Extra-Long
- F175XCB- Integrated Hydraulic Steering(IHS) for Digital Electronic Control(DEC) Helm, TotalTilt with Tilt Limiter, Transom height - Extra-Long

General Features:

- 4-Stroke, 16 Valve DOHC Direct Action In-Line 4
- Integrated Hydraulic Steering(IHS) for Mech Helm
- Power Trim & Tilt with integrated Tilt Limiter
- Direct Injection - higher reliability and increased performance
- High Output Alternator - 50 amps at wide open throttle or 22 amps at 600 RPM
- Offset Crankshaft - More efficient transfer of power

Price includes:

- Outboard
- Integrated Hydraulic Steering(IHS) for Mech Helm
- Integrated Tilt Limiter
- Water test



- Free prop exchange

Price does not include:

- Yamaha Stainless Steel Shift Dampener System(SDS) Prop
- Yamaha 703 Side Control Box and Yamaha looms/wiring
- 2x Yamaha multi function digital gauges(Tacho and Speedo, Fuel level, Battery level, Trim, Hours, Warnings, etc)
- Battery, Steering, Fuel filter, Fuel tank

Specifications

Engine Type

4-Stroke, 16 Valve DOHC Direct Action In-Line 4
Displacement2785 cc
Bore x Stroke96.0 x 96.2 mm
Recommended Max RPM5000-6000
Lubrication SystemWet Sump
Fuel ManagementElectronic Fuel Injection(EFI)
IgnitionTransistor Controlled Ignition(TCI)
Starter SystemElectric
Alternator Output50A. 50A at wide open throttle or 22A at 600RPM
Operation MethodRemote Control(Forward Control)
Trim & Tilt MethodPower Trim & Tilt with integrated Tilt Limiter
Digital Network GaugesOptional
Gear Ratio1.86:1

Dimensions

Transom Length

- F175LB:516(20.4)
- F175XB: 642(25.3)
- F175XCB: 642(25.3)

Weight

- F175LB:223kg
- F175XB: 234kg
- F175XCB: 235kg

Prices do not include fitting or accessories where applicable.

It is a Yamaha Australia stipulation that all Yamaha Outboards be fitted and personally delivered by the selling Yamaha outboard dealership.

Boat Brand	Model	Stock Number
Yamaha	F175LB	0
Length	Year	Condition
0.00 Metres	2024	New
State	City	Boat Link
California	Los Angeles	