



F20SMHB Yamaha 4 Stroke 20hp Short Shaft, Manual Start, Mechanical Trim & Tilt System, Battery-Less Electronic Fuel Injection, Tiller Handle PORTABLE OUTBOARD FOR SALE

OUR PRICE: \$3137.98



Description

F20SMHB Yamaha 4 Stroke 20hp Short Shaft, Manual Start, Mechanical Trim & Tilt System, Battery-Less Electronic Fuel Injection, Tiller Handle PORTABLE OUTBOARD FOR SALE

The new F20 is built around the award winning F25, an Innovation Award-winning outboard that immediately set the industry standard. Modified ECU mapping and a redesigned camshaft allows the new F20 to harness the huge potential of this outboard and to optimize its performance.

The result is an exceptionally strong outboard with the versatility to power a wide variety of boats.

The new F20 delivers fast acceleration and enhanced boat performance under load, so when it's time to hit the water, you won't have to leave anything (or anyone) behind. The variable trolling rpm switch makes the F20 the perfect fishing companion, while the easy to use fresh water flush attachment makes the engine a breeze to clean at the end of the day. Built-in ergonomic carry handles and two-position resting pads make it easy to remove and store the F20.

Customers can choose manual start configuration, using Yamaha's battery-less EFI technology, to power their boat with minimum rigging requirements.

Yamaha offers a range of electric-start configurations, all with the added peace of mind of factory installed manual pull start. Available in:

- F20SMHB- Manual Start, Tiller Handle, Transom height - Standard
- F20LMHB- Manual Start, Tiller Handle, Transom height - Long
- F20SWPB- Electric Start, Multi-Functional Tiller Handle or Power Tilt System(Forward Control), Transom height - Standard
- F20LWPB- Electric Start, Multi-Functional Tiller Handle or Power Tilt System(Forward Control), Transom height - Long

General Features:POWER/PERFORMANCE

- Enhanced Acceleration and Performance Under Load
- Single Overhead Camshaft
- Battery-less Electronic Fuel Injection
- Wide-Span Mounting System

RELIABILITY/DURABILITY

- CDI Microcomputer
- Wet Sump Lubrication
- Engine Warning System
- Mechanical Single Throttle Valve Intake System

Disclaimer

Our company offers the details of this vessel in good faith but cannot guarantee or warrant the accuracy of this information nor warrant the condition of the vessel. A buyer should instruct his agents and/or surveyors to investigate such details buyer desires validated. This vessel is offered subject to prior sale, price change or withdrawal without notice.



- SST Drive, Prop, Shift Shafts
- SST Steering Tube
- Magnetic Drain Plug
- Sacrificial Anodes
- YDC-30 Aluminum Alloy
- Phaze Five™ Paint System
- Electro-deposited Powerhead Paint Process

CONVENIENCE/CONTROL

- High-Output (16-Amp) Alternator
- Electric and Pull-Start Available Together (some models)
- Retrofit Electric Start Available
- 45-Degree Steering in both Directions
- Built-In Resting Pads and Carry Handles
- Variable Trolling RPM Switch (VTS®)
- Freshwater Flush
- Spin-on Oil Filter
- Offset Steering Friction Lever
- Auto Decompression Device
- Vibration Reduction Mounting System
- C.A.R.B. Ultra Low Emissions 3 Star Rating
- External Oil Drain Plug

Specifications

ENGINE

Engine Type Two-cylinder, In-line

Displacement 432 cc

Bore x Stroke 65 x 65.1 mm

Full Throttle RPM Range 5000 - 6000

Variable Trolling RPM Range 750-1050 rpm

750-1050 rpm 900 rpm

Horsepower Rating at Propshaft 20 hp at 5500 rpm

Compression Ratio 9.3:1

Fuel Induction/Scavenging SOHC, 2 valves per cylinder

Alternator Output 16 amp

Starting Method Manual

Ignition CDI Microcomputer

Lubrication Wet Sump

Degree of Trim 4 positions (manual operation)

Degree of Tilt -4 through +62° (manual tilt)

Exhaust Through Propeller

Cooling Water, Thermostatic Control

DRIVE

Gear Shift F-N-R (Forward-Neutral-Reverse)

Gear Ratio 2.08:1

SHAFT LENGTH

See Model Code S=15" L=20"

FUEL AND LUBRICATION

Recommended Fuel Regular Unleaded

Recommended Fuel Filtration Yamaha 10-Micron or Mini-10™

Recommended Oil Yamalube® 4-M 10w-30

Engine Oil Capacity 1.1L / 1.0L (w/without filter)

LIMITED WARRANTY

Recreational ☐☐☐ 2 + 2 Years

Commercial ☐☐☐ 1 Year

WEIGHT

- F20SMHB = 57 kg
- F20LMHB = 59 kg
- F20SWPB = 62 kg
- F20LWPB = 64 kg

*Weight estimated at time of publishing includes standard propeller, which is included with this model. Weight is measured without motor and gearcase oil.

Prices do not include fitting or accessories where applicable.

It is a Yamaha Australia stipulation that all Yamaha Outboards be fitted and personally delivered by the selling Yamaha outboard dealership.

Boat Brand	Model	Stock Number
Yamaha	F20SMHB	0
Length	Year	Condition
0.00 Metres	2024	New

Disclaimer
 Our company offers the details of this vessel in good faith but cannot guarantee or warrant the accuracy of this information nor warrant the condition of the vessel. A buyer should instruct his agents and/or surveyors to investigate such details buyer desires validated. This vessel is offered subject to prior sale, price change or withdrawal without notice.

Phone: +1 (323) 9048193

Email: online@fame2saoutboard.com

Website: <https://www.brisbaneyamaha.com.au>

SF Industrial Ave, Los Angeles, CA, 90034, USA



State	City	Boat Link
California	Los Angeles	